

KNX/EIB LM2 feature matrix

Feature / Product	KNX/EIB LogicMachine 2 FULL	KNX/EIB LogicMachine 2 + Modbus	KNX/EIB LogicMachine 2 + EnOcean	KNX/EIB LogicMachine 2 + GSM	KNX/EIB LogicMachine 2 Visualization	KNX IP Router with Logging
Hardware	Embedded, ARM9 400MHz					
Mounting type	DIN 3P					
Hardware watchdog timer	x					
Software watchdog timer	x					
Group address control	x					
KNX bus events logger	x					
Max object/event count to control	Unlimited					
Object logging (SQL database on-board)	x					
Unlimited connections	x					
IP interface (access bus from ETS)	x					
USB interface support	2					
FT1.2 interface on-board	x					
RS485 interface on-board	1 or 3 (depends on IO count)				-	-
Import/Export workspace	x					
Import project from ETS	x					
Different language support	x					
Touch device visualization	Android/iOs/* based <i>*all browsers supported built on webkit engine</i>					
Own icon integration	x					
Visualization creation and edit	WEB					
SCADA Multi-user support	x					
Multi-level access control	x					
Full system backuping (scripting, DB, objects)	x					
System replication	x					
IP Streaming video integration	x					
Graphics trends support	x					
SCADA Visualization	x					
Logic engine based on events	x	-	-	-	-	-
Logic engine based on date/time	x	-	-	-	-	-
Logic Engine based on residential tasks	x	-	-	-	-	-
Alarms	x	-	-	-	-	-
Scripting language	LUA	-	-	-	-	-
Sunrise/sunset function	x	-	-	-	-	-
RDF channels	x	-	-	-	-	-
Custom logs	x	-	-	-	-	-
PID, PI regulators	x	-	-	-	-	-
Drag&drop programming helper with code snippets on-board	x	-	-	-	-	-
Other network protocol support (SMTP, SNMP, XMPP etc.)	In Box	-	-	-	-	-
No-limited integration with web-services	x	-	-	-	-	-
Secure tunneling	x	-	-	-	-	x
OBIX support	x	-	-	-	-	-
Logic module functionality	x	-	-	-	-	-
Line/Area coupler functionality	x	-	-	-	-	x
IP Router functionality	x	-	-	-	-	x
EnOcean gateway support (USB)	x	-	x	-	-	-
GSM gateway support (USB) with integrated SMS/GPRS message treatment	x	-	-	x	-	-
Modbus gateway in-box	x	x	-	-	-	-
DALI gateway (through ext. device)	x	-	-	-	-	-
DMX gateway in box	x	-	-	-	-	-
Analog/binary input	4 or 1 (depends on RS485 count)				-	-
Thermostat	logic engine	-	-	-	-	-
Water leakage detection functionality	using IO and logic engine	-	-	-	-	-
Binary/Open collector output for external relay control etc.	4 or 1 (depends on RS485 count)				-	-
Shutter control functionality	logic engine	-	-	-	-	-
Fancoil control functionality	logic engine	-	-	-	-	-
Scenes support	logic engine	-	-	-	-	-
Constant Lighting Control	logic engine	-	-	-	-	-
Audio controller	logic engine	-	-	-	-	-
Price, EUR w/o VAT	790	490	490	490	440	390

SW, HW, GW

SENSORS

ACTUATORS

