



Stereomicroscope, with precision fixed arm, 10x - 20x - 40x, touch panel, with rechargeable battery

| <b>Observation Method -</b>            |  |   |
|--|--|---|
| Transmitted Light                      | Brightfield                                  | Yes                                       |
| J                                      |  |   |
| Observation Method -<br>Incident Light | Brightfield                                  | Yes                                       |
| Head                                   | Туре   | Binocular                                 |
|  | Construction material                        | Aluminum & Plastic molds / Aluminum gears |
|  | Inclination                                  | 45°                                       |
|  | Interpupillary distance (mm)                 | 53-75                                     |
|  | Dioptric adjustment                          | On both tubes                             |
|  | Fixing screw for eyepieces                   | Yes                                       |
|  | Tube inner diameter (mm)                     | 30.5                                      |
|  |  |   |
| Eyepieces                              | Field number (mm)                            | 20  |
|  | Magnification                                | 10x                                       |
|  | Micrometric scale                            | As optional                               |
|  | Diameter of micrometer glass (mm)            | 20  |
|  | Rubber cup                                   | Yes                                       |
|  | · · · ·                                      |   |
| Objective                              | Optical system                               | Greenough                                 |
|  | Anti-fungus treatment                        | Yes                                       |
|  | Objective Type                               | Achromatic                                |
|  | Working distance (mm)                        | 60  |
|  | Standard magnifications                      | 10x, 20x, 40x (rotating turret)           |
|  |  |   |
| Focusing System                        | Туре   | Coarse                                    |
|  | Coarse total travel (mm)                     | 41  |
|  | Adjustable tension                           | Yes                                       |
|  |  |   |
| Stand                                  | Туре   | Precision fixed arm                       |
|  | Handle                                       | Yes                                       |
|  |  |   |
| Stage                                  | Frosted diffusion plate for transmitted ill. | Yes, diameter 60 mm                       |
|  | Black/white contrast plate for incident ill. | Yes, diameter 60 mm                       |
|  | Specimen clips                               | Yes                                       |
|  |  |   |
| Transmitted<br>Illumination            | Туре   | LED                                       |
|  | Light source power (W)                       | 1   |
|  | Brightness control                           | Touch Panel                               |
|  | Lifetime (hours)                             | > 65,000                                  |
|  | Temperature (K)                              | 6,300                                     |
|  | Max. required power (W)                      | 1.5                                       |

|                                  | <b>_</b>                           |                                |
|----------------------------------|------------------------------------|--------------------------------|
| Incident Illumination            | Туре                               | LED                            |
|                                  | Light source power (W)             | 1                              |
|                                  | Brightness control                 | Touch Panel                    |
|                                  | Lifetime (hours)                   | > 65,000                       |
|                                  | Temperature (K)                    | 6,300                          |
|                                  | Max. required power (W)            | 1.5                            |
|                                  |                                    |                                |
| Power Supply for<br>Illumination | Туре                               | External                       |
|                                  | Microscope connector               | Jack, 2.1 mm                   |
|                                  | Power plug type                    | Multi-plug (EU, UK, US)        |
|                                  | Input voltage                      | 100/240 Vac, 50/60 Hz          |
|                                  | Output voltage                     | 5 Vdc 500 mA                   |
|                                  | LED indicator                      | Yes                            |
|                                  | Rechargeable batteries             | Yes                            |
|                                  | Battery type                       | Ni-MH (3x, AA size)            |
|                                  | Working time of batteries (hours)  | up to 8                        |
|                                  | Charging time of batteries (hours) | 8                              |
|                                  |                                    |                                |
| Accessories Included             | Dust cover                         | Yes                            |
|                                  | Immersion oil (10ml)               | No                             |
|                                  | Tension adjustment tool            | Yes                            |
|                                  | User Manual                        | Digital version (downloadable) |
|                                  |                                    |                                |
| Additional Information           | Maximum sample height (mm):        | 35                             |
|                                  | L                                  |                                |
|                                  |                                    |                                |
| Product Dimensions               | Total height (mm)                  | 288                            |
|                                  | Base height (mm)                   | 45                             |
|                                  | Base width (mm)                    | 183                            |
|                                  | Base depth (mm)                    | 205                            |
|                                  |                                    |                                |
| Product Weight                   | (kg)                               | 2                              |
|                                  |                                    |                                |