



ATLANTIS GEOMETRY, TIRE CAPACITY, BRAKE SPECS*

BB DROP mm	TT UPSLOPE degrees	Rear Hub Space mm	APPROX. Standover at mid TT** cm	ST angle degrees	HT angle degrees	Rake mm	Top Tube cm	Chain stay cm	WHEEL SIZE mm/nominal	RECOMMENDED MIN. TIRE radius mm/nominal	RECOMMENDED MAX. TIRE radius mm/nominal	EFFECTIVE BRAKE REACH	BRAKE STYLE	
47	48	2.5	135	71.2	72.5	71	4.5	52	44	559/26-IN.	310/26x1.25	328/26x1.85	N/A	CANTI
51	48	2.5	135	77	72.5	72	4	53.5	44	559/26-IN.	310/26x1.25	340/26x2.35	N/A	CANTI
53	48	2.5	135	78.9	72.5	72	4	55	44	559/26-IN.	310/26x1.25	340/26x2.35	N/A	CANTI
54.5	48	2.5	135	80.8	72	72	4	56	44	559/26-IN.	310/26x1.25	340/26x2.35	N/A	CANTI
56	48	2.5	135	81.7	72	72	4	57	44	559/26-IN.	310/26x1.25	340/26x2.35	N/A	CANTI
58	80	2.5	135	83.2	72	72	4.5	58.5	45.5	622/700C	345/700x32	365/700x55	N/A	CANTI
61	80	2.5	135	85.1	72	72	4.5	59	45.5	622/700C	345/700x32	365/700x55	N/A	CANTI
64	80	2.5	135	87	72	72	4.5	60	45.5	622/700C	345/700x32	365/700x55	N/A	CANTI
66	80	2.5	135	88.9	72	72	4.5	61	45.5	622/700C	345/700x32	365/700x55	N/A	CANTI
68	80	2.5	135	90.8	72	72	4.5	62	45.5	622/700C	345/700x32	365/700x55	N/A	CANTI

grant@rivbike.com